



// Reaction



KÖSTER IN 8

Start of reaction approx. 30 sec
 Full reaction time approx. 240 sec
 Tack-free approx. 330 sec
 Expansion volume approx. 1 : 40
 Reaction temperature approx. 38 °

KÖSTER IN 8 + 10% accelerator

Start of reaction approx. 6 sec
 Full reaction time approx. 60 sec
 Tack-free approx. 120 sec
 Expansion volume approx. 1 : 60
 Reaction temperature approx. 43 °C

Key features at a glance

- Single component
- Water-reactive polyurethane pre-polymer
- Only reacts in contact with water
- Spontaneously forms a firm, tough-elastic, water proof polyurethane foam
- Is able to follow crack movements and waterproofs permanently without post-injection with a solid-body resin
- 30-fold increase in volume
- Resistant to hydrolysis
- Accelerator available for an even faster reaction

KÖSTER

KÖSTER at your service – worldwide.



DEUTSCHE
BAUCHEMIE



// Contact us

KÖSTER BAUCHEMIE AG
 Dieselstraße 1–10 · 26607 Aurich
 Tel.: +49 4941 9709 0
 E-Mail: info@koster.eu
www.koster.eu

Follow us on social media:




Issued: 6/2025

KÖSTER

KÖSTER IN 8

One component water-reactive foam
for crack injection



Single component – can be directly injected

Reacts immediately on contact with water

For pressurized and non-pressurized water leakages

MADE IN
GERMANY

// Processing



- 1 Drill holes along the course of the crack on alternate sides at a distance of approx. 10-15 cm and at an angle of approx. 45° towards the crack.



- 3 KÖSTER IN 8 is poured directly into the hopper of the injection pump. No mixing necessary.



- 5 When finished, clean the pump with KÖSTER PUR Cleaner.



- 2 Install KÖSTER Superpackers in every second or third borehole. The unclosed boreholes allow pressure release during injection.



- 4 Inject KÖSTER IN 8 into the crack proceeding from bottom to top.



- 6 Close the boreholes with a mortar e. g. KÖSTER KB-Fix 5.

// Areas of application



- Stopping fast large water leakages with foaming action
- Waterproofing horizontal and vertical cracks
- Filling cavities and voids in masonry and concrete
- Sealing wall-floor joints
- Creating a flexible bond

// Related products

KÖSTER IN 8
Viscoelastic, single-component water-reactive PU injection foam. Filler-free, hydrolysis and acid resistant.

KÖSTER IN 8 Accelerator
Accelerator for KÖSTER IN 8 injection foam

KÖSTER Superpacker 13 mm x 130 mm CH
The KÖSTER Superpacker provides a very high contact pressure to the borehole due to the cone-shaped center of the tightening mechanism.

KÖSTER 1C Injection Pump
Electrical 1C injection pump for injecting of cracks and voids. It is suitable for the injection of all KÖSTER injection materials (foams and resins).